



Prefabricated lifting station for clean and grey water according to EN 12050-2 standard

FLYGT MICRO 4 Series



MARKET SECTORS DOMESTIC.

APPLICATIONS

- Suitable for delivering clean and grey water to main sewer lines located at a higher level, or where gravity drainage is not possible.

SPECIFICATIONS


- The station is equipped with:
 - Polyethylene **basin** with a capacity of 110 litres, equipped with a threaded cover.
 - **Cable glands** for power supply cables (and floats).
 - Rp 1 1/4 or Rp 1 1/2 **delivery pipes** with fast connection and ring nut for easy disassembly of the pump.
 - **3 fast connections:**
 - 1 x DN110 for inlet,
 - 1 x DN50 for ventilation and
 - 1 x DN65 for cable connection.
 - **1 x DN50** fast connection for the manual pump.
 - **DOC or DOMO 7 submersible pump**, vortex or channel impeller type.
- Versions with **vortex impeller** suitable for:
 - clean water, effluent, sewage containing suspended solids and fibres but non-faecal wastewater.
- Versions with **single or twin channel impeller** suitable for:
 - clean water, effluent, sewage not containing suspended fibres and faecal wastewater.
- **MICRO 4** can be installed on the floor or buried in a suitable structure following instructions in the "Instructions and Operative Manual".
- **Easy installation:**
 - installation is quick and easy: for the single-phase versions you just connect the pipes and the electrical cables.
 - The new **MICRO 4** is provided with side handles for ease of handling.
 - Pre-installed delivery pump and unions.
- **Ecological solution:**
 - tank made from 100% recyclable polyethylene.
- **Easy maintenance and repair.**
 - Tried and tested pump technology.
 - Pump quick and easy to remove thanks to the ring nut located near the cover.

ACCESSORIES

- Ball check valves.
- Alarm kit.
- Connector kit.
- Manual pump.
- Control panel.



IDENTIFICATION CODE



EXAMPLE : MICRO 4 DOMO 7VX
Lifting station MICRO 4 series with DOMO 7VX submersible electric pump.